

PRODUCT SPECIFICATIONS

DVM IM



Specifications

DVM IM - Marine Grade Enclosed Tracking System - (Up to 50 ft.lb. Load Torque)

PHYSICAL DIMENSIONS	Standard: 27.5" x 29.7"
WEIGHT	50 lbs. (est.)
ENVIRONMENTAL	Standardized to IP-66
OPERATING TEMP*	Standard: -40°C - 65°C Optional: -50°C - 65°C
OPERATING POWER	Peak: 100 Watts Standby: 10 Watts
PAN/TILT-AXIS RANGE*	360° Continuous (PAN) ±20° (TILT)
PAN/TILT-AXIS SPEED	Up to 10°/sec (PAN) Up to 5°/sec (TILT)
MOUNTING*	3" - 4" Pole Mount (Required)
OPERATING VOLTAGE	PoE: 48 VDC DC: 20 - 50 VDC w/Auto (48V Nominal)
NETWORK PORTS	(10/100 Mbps)
Components & Accessories	
GPS TARGETING STABILIZER	GPS-Based Signal Targeting & Stabilization
FLEET CONTROLLER	Control Appliance for Multiple Control Units
POWER CABLING	DC Power Cables, Available up to 330 ft.
MIL-SPEC CABLING	Insulated Cat 5e Cabling, Available up to 330 ft.
MOUNTING HARDWARE	Universal Pole Mount Kits, Radio Mount Kits

*Additional Components Required

Made In USA



www.batswireless.com

8431 Georgetown Rd. #600
Indianapolis, Indiana 46268

Toll Free +1-888-955-8228
Sales +1-317-500-4507
Support +1-317-500-4506
Email info@batswireless.com